TUNGSRAM

Innovation is our heritage EST. 1896





LED Pygmy
LED2.1/T25/827/100-240V/E14/F 2/20
HB
93119702

Product information

A product line to suit special purpose applications in confined spaces, cabinets and fridge lighting, a great replacement for traditional alternatives of lower energy efficiency. The employment of traditional Pygmy lamps – except for the oven Pygmy -, according to official regulation, is to be banned in the EU, UK and Turkey from the 1st of September 2021. We are extending our range with a higher lumen output version to support the transition from traditional to LED lamps, keeping the price the closest possible to the original level.

Application areas







Product data

93119702
LED2.1/T25/827/100-240V/E14/F 2/20 HB
93119718 - LED2.1/T25/827/100-240V/E14/F 2/20 HB DS
59
12.5
Tungsram
E14

Performance data

Rated efficacy [lm/W] 90.4761904761905 Energy efficiency class (EEC) F Rated life L70/B50 [h] 15000 Input Frequency [Hz] 50/60 Nominal correlated colour temperature (CCT) [K]] 2700 Nominal lumens [lm] 190 Colour Rendering Index (CRI) [Ra] 80 Flicker and Stroboscopic Visibility Measure (SVM) 0.4	Color consistency (SDCM)	6
Rated life L70/B50 [h] 15000 Input Frequency [Hz] 50/60 Nominal correlated colour temperature (CCT) [K]] 2700 Nominal lumens [lm] 190 Colour Rendering Index (CRI) [Ra] 80	Rated efficacy [lm/W]	90.4761904761905
Input Frequency [Hz] 50/60 Nominal correlated colour temperature (CCT) [K]] 2700 Nominal lumens [lm] 190 Colour Rendering Index (CRI) [Ra] 80	Energy efficiency class (EEC)	F
Nominal correlated colour temperature (CCT) [K]] 2700 Nominal lumens [lm] 190 Colour Rendering Index (CRI) [Ra] 80	Rated life L70/B50 [h]	15000
Nominal lumens [lm] 190 Colour Rendering Index (CRI) [Ra] 80	Input Frequency [Hz]	50/60
Colour Rendering Index (CRI) [Ra] 80	Nominal correlated colour temperature (CCT) [K]]	2700
	Nominal lumens [lm]	190
Flicker and Stroboscopic Visibility Measure (SVM) 0.4	Colour Rendering Index (CRI) [Ra]	80
	Flicker and Stroboscopic Visibility Measure (SVM)	0.4

Electrical data

Nominal lamp power factor	>0.12
Operating Temperature (MIN) [°C]	-20
Operating Temperature (MAX) [°C]	40
Starting time (sec)	<1
Number of switching cycles	50000
Nominal lamp voltage range [V]	100-240
Nominal power [W]	2.1



Logistic data

Shipment	Standard
DUN Code	15994100083112
EAN Code	5994100083115
Pack Quantity	2/20
Product status	Available

Downloads & Links

Go to the catalog site (HTTP)
Link to EPREL (HTTP)
Datasheet (PDF)
Images (HTTP)
DoC document (PDF)
Gen1 datasheet (PDF)