



11

kWh/1000h

115

lumens/watt

## LED Plug In 4Pin Gen2

LED 10/G2/G24q-3/4P/H/830 TU BX1/6  
93110771

---

### Product information

LED 4 Pin Plug-In lamp offers safe, reliable and affordable energy saving alternative to Compact Fluorescent 4 Pin Plug-In lamps used in downlight fixtures. The replacement can be completed without tools or costly upgrade. The new GEN2 4Pin LED Plug-In lamp is available in 7.5W and 10W to replace 18W (G24q-2) and 26W (G24q-3) regular CFL lamps. The new lamp is designed for horizontal applications.

---

## Product data

|                                    |            |
|------------------------------------|------------|
| Product Code                       | 93110771   |
| Burn Position                      | Horizontal |
| Bulb Diameter [mm]                 | 34.5       |
| Bulb maximum overall diameter [mm] | 34.5       |
| Maximum Overall Length [mm]        | 162        |
| Arc Gap                            | Horizontal |
| Net weight per piece [g]           | 125        |
| Gross weight per piece [g]         | 147        |
| Operating position                 | Horizontal |
| Mercury Content [mg]               | 0mg        |
| RoHS compliant                     | Yes        |
| Brand                              | TungsrAm   |
| Cap/Base                           | G24q-3     |

## Performance data

|   |                   |
|---|-------------------|
| Nominal/ Rated Beam Angle [°]                   | 110 x 120         |
| Color consistency (SDCM)                        | <6 steps          |
| Colour Code                                     | 830               |
| Weighted energy consumption [kWh/1000h]         | 11.0              |
| Rated efficacy [lm/W]                           | 115               |
| Rated efficacy 25°C HF preheat                  | 118 x 80 x 178 mm |
| Energy efficiency class (EEC)                   | F                 |
| Rated life L70/B50 [h]                          | 50000             |
| Nominal correlated colour temperature (CCT) [K] | 3000              |
| Nominal lumens [lm]                             | 1150              |
| Colour Rendering Index (CRI) [Ra]               | 80                |

## Electrical data

|                                    |                |
|------------------------------------|----------------|
| Operating Temperature [°C]         | -20C ... +40C  |
| Operating Temperature (MIN) [°C]   | -20            |
| Operating Temperature (MAX) [°C]   | 40             |
| Starting ambient temperature range | -20°C to +40°C |
| Startup time [sec]                 | <0.5           |
| Number of switching cycles         | 30000          |
| Dimming Capability                 | No             |
| Nominal power [W]                  | 10             |

## Logistic data

|                          |                   |
|--------------------------|-------------------|
| Shipment                 | Standard          |
| DUN Code                 | 15994100028250    |
| EAN Code                 | 5994100028253     |
| Pack Quantity            | 6                 |
| Inner pack type          | Bx                |
| Outer pack type          | outer bx          |
| Layer quantity           | EL 600 / UL 672   |
| Layer quantity EUR       | 600               |
| Layer quantity UK        | 672               |
| Pallet quantity EUR (PC) | 3600              |
| Pallet quantity UK (PC)  | 4032              |
| Outer case size          | 118 x 80 x 178 mm |
| Product status           | Available         |

## Downloads & Links

[Go to the catalog site \(HTTP\)](#)

[Images \(HTTP\)](#)

[LED PlugIn compatibility ballasts \(HTTP\)](#)

[Datasheet \(FR\) \(PDF\)](#)

